



SDS #: 418

Revision Date: March 25, 2014

Isobutyl Alcohol Safety Data Sheet (SDS)

SECTION 1 — CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Isobutyl Alcohol

Signal Word
DANGER

Flinn Scientific, Inc. P.O. Box 219, Batavia, IL 60510 (800) 452-1261

Chemtrec Emergency Phone Number: (800) 424-9884

Pictograms

SECTION 2 — HAZARDS IDENTIFICATION

Hazard class: Flammable liquids (Category 3). Flammable liquid and vapor (H226). Keep away from heat, sparks, open flames, and hot surfaces. No smoking (P210).



Hazard class: Acute toxicity, oral (Category 5). May be harmful if swallowed (H303).



Hazard class: Skin and serious eye damage, corrosion or irritation (Category 2, 2A). Causes skin and serious eye irritation (H315+H319).



Hazard class: Specific target organ toxicity, single exposure; respiratory tract irritation (Category 3). May cause respiratory irritation (H335). Avoid breathing mist, vapors or spray (P261).

Hazard class: Specific target organ toxicity, single exposure; Narcotic effects (Category 3). May cause drowsiness or dizziness (H336).

SECTION 3 — COMPOSITION, INFORMATION ON INGREDIENTS

Component Name	CAS Number	Formula	Formula Weight	Concentration
Isobutyl alcohol	78-83-1	(CH ₃) ₂ CHCH ₂ OH	74.12	
Synonyms: 2-Methyl-1-propanol				

SECTION 4 — FIRST AID MEASURES

Call a POISON CENTER or physician if you feel unwell (P312).

If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing (P304+P340).

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so.

Continue rinsing (P305+P351+P338). **If eye irritation persists eyes:** Get medical advice or attention (P337+P313).

If on skin or hair: Immediately remove all contaminated clothing. Rinse skin with water (P303+P361+P353). **If skin irritation occurs:** Get medical advice or attention (P332+P313).

If swallowed: Rinse mouth. Call a POISON CENTER or physician if you feel unwell.

SECTION 5 — FIRE FIGHTING MEASURES

Class IC flammable liquid.

NFPA Code

Flash point: 28°C Flammable limits: Lower: 1.7% Upper: 10.6% Autoignition Temperature: 415 °C

H-2

F-3

R-0

When heated to decomposition, may emit toxic fumes.

In case of fire: Use a tri-class dry chemical fire extinguisher (P370+P378).

SECTION 6 — ACCIDENTAL RELEASE MEASURES

Remove all ignition sources and ventilate area. Contain spill with sand or other inert absorbent material; deposit in sealed bag or container. See Sections 8 and 13 for further information.

SECTION 7 — HANDLING AND STORAGE

Flinn Suggested Chemical Storage Pattern: Organic #2. Store with alcohols, glycols, amines and amides. Store in a dedicated flammables cabinet. If a flammables cabinet is not available, store in Flinn Saf-Stor™ can. Keep container tightly closed (P233). Keep cool (P235). Use only in a hood or well-ventilated area (P271).

SECTION 8 — EXPOSURE CONTROLS, PERSONAL PROTECTION

Wear protective nitrile (not latex) gloves, protective clothing, and eye protection (P280). Wash hands thoroughly after handling (P264). Use only in a hood or well-ventilated area (P271).

Exposure guidelines: PEL 300 mg/m³ (OSHA); TLV 152 mg/m³ (ACGIH)

SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

Colorless liquid. Distinctive odor like alcohol.	Boiling point: 108 °C
Soluble: Alcohol and ether. Slightly in water.	Flash point: 37.7 °C
	Melting point: -101.9 °C
	Refractive index: 1.3955
	Specific gravity: 0.8018

SECTION 10 — STABILITY AND REACTIVITY

Avoid contact with strong oxidizers, acid chlorides, and acid anhydrides.

Shelf life: Indefinite, if stored properly.

SECTION 11 — TOXICOLOGICAL INFORMATION

Acute effects: Severe irritant.	ORL-RAT LD ₅₀ : 2460 mg/kg
Chronic effects: Dermatitis.	IHL-RAT LC ₅₀ : N.A.
Target organs: N.A.	SKN-RBT LD ₅₀ : 3400 mg/kg

SECTION 12 — ECOLOGICAL INFORMATION

P273 Avoid release to the environment.

SECTION 13 — DISPOSAL CONSIDERATIONS

Please review all federal, state and local regulations that may apply before proceeding.

Flinn Suggested Disposal Method #18b is one option.

SECTION 14 — TRANSPORT INFORMATION

Shipping name: Isobutyl alcohol. Hazard class: 3, Flammable liquid. UN number: UN1212.

SECTION 15 — REGULATORY INFORMATION

TSCA-listed, EINECS-listed (201-148-0), RCRA code U140.

SECTION 16 — OTHER INFORMATION

This Safety Data Sheet (SDS) is for guidance and is based upon information and tests believed to be reliable. Flinn Scientific, Inc. makes no guarantee of the accuracy or completeness of the data and shall not be liable for any damages relating thereto. The data is offered solely for your consideration, investigation, and verification. The data should not be confused with local, state, federal or insurance mandates, regulations, or requirements and CONSTITUTE NO WARRANTY. Any use of this data and information must be determined by the science instructor to be in accordance with applicable local, state or federal laws and regulations. The conditions or methods of handling, storage, use and disposal of the product(s) described are beyond the control of Flinn Scientific, Inc. and may be beyond our knowledge. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR

LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THIS PRODUCT(S).

N.A. = Not available, not all health aspects of this substance have been fully investigated.

N/A = Not applicable

Consult your copy of the Flinn Science Catalog/Reference Manual for additional information about laboratory chemicals.

Revision Date: March 25, 2014
